

# TV AMPLIFIER Serie 9000

General		
Power supply (cod. 2109 opt*)	VDC	12
Power consumption	W	1.4 (min) ÷ 2.4 (max)
Total remote power	mA	100 (12 V)
Dimension	mm	97x81x18

Model	Description	Gain	Output level	BIV [ch]	BV [ch]
<b>OUTPUT LEVEL 112dBuV</b>					
9100	5 Inputs TV Amplifier BI-BIII UHF-BIV-BV	20dB 22dB	112dBuV	21, 36	39, 69
9101	5 Inputs TV Amplifier BI-BIII UHF-BIV-BV	20dB 22dB	112dBuV	21, 32	35, 69
9102	5 Inputs TV Amplifier BI-BIII UHF-BIV-BV	20dB 22dB	112dBuV	21, 38	41, 69
9110	1 Inputs TV Amplifier (VHF + UHF)	20dB VHF 25dB UHF	112dBuV	---	---
9120	2 Inputs TV Amplifier VHF UHF	20dB 25dB	112dBuV	---	---
9130	3 Inputs TV Amplifier VHF UHF - UHF	20dB 23dB	112dBuV	---	---
<b>OUTPUT LEVEL 116dBuV</b>					
9200	5 Inputs TV Amplifier BI-BIII UHF-BIV-BV	30dB 30dB	116dBuV	21, 36	39, 69
9201	5 Inputs TV Amplifier BI-BIII UHF-BIV-BV	30dB 30dB	116dBuV	21, 32	35, 69
9202	5 Inputs TV Amplifier BI-BIII UHF-BIV-BV	30dB 30dB	116dBuV	21, 38	41, 69
9210	1 Inputs TV Amplifier (VHF + UHF)	30dB VHF 32dB UHF	116dBuV	---	---
9220	2 Inputs TV Amplifier VHF UHF	30dB 32dB	116dBuV	---	---
9230	3 Inputs TV Amplifier VHF UHF - UHF	30dB 30dB	116dBuV	---	---

## \*AC/DC adaptor 2109

Freq. Range	5-2150 MHz
DC output (RF-in)	12V 400mA
AC input	100~240V 50/60Hz 0.25A max
Trunk Loss TV	0.4dB [40~860MHz]
Trunk Loss SAT	1.0dB [950~2150MHz]

