

Catalogue

# WOW!

## World of Weller®



# Soldering Irons and Tips

## Electronically Controlled Low Voltage Soldering Irons



NT Soldering tips: see page 94

Order No.	Model	Description
005 33 159 99	WMPT	<b>Soldering set 65 W, 24 V</b> <b>Safety rest with Stop+Go function and integrated dry cleaner only for digital soldering stations</b>

consists of:

WMP	WMP	Micro Soldering Iron 65 W, 24 V with soldering tip NT 1
005 15 162 99	WDH 20T	Safety rest with Stop+Go function and dry cleaner WDC 2



NT Soldering tips: see page 94

Order No.	Model	Description
005 29 179 99	WMP	<b>Soldering set 65 W, 24 V,</b> <b>Comfort safety rest with 4 step varying inclination</b> The Soldering Iron WMP fullfills ambitious SMD soldering tasks with its extreme quick heat-up time. The soldering tip holder is integrated into the grip and allows a short distance of tip-to-grip. Placed in the ergonomic safety rest WDH 20 the varying inclination of the iron can be adjusted in 4 individual steps. The reverse side is able to carry up to three NT-soldering tips.

consists of:

WMP	WMP	Micro Soldering Iron 65 W, 24 V with soldering tip NT 1
005 15 122 99	WDH 20	Safety rest

### Weller WDC – Dry Cleaner



Order No.	Model	Description
005 15 124 99	WDC	<b>Weller WDC – Dry Cleaner</b> The solution for cleaning from lead free solder! For further information see page 180.

















Accessory:


005 13 824 99		Metal wool WDC replacement (2 pieces)
---------------	--	---------------------------------------



## NT Soldering Tip Series

### Soldering Tips for WMP

Order-no.	Model	Description	Width A	Thickness B	Length L		
NT 1SC	<b>NT 1SC</b>	Chisel tip slim	0,4 mm	0,15 mm	14 mm		
NT H	<b>NT H</b>	Chisel tip	0,8 mm	0,4 mm	8,4 mm		
NT K	<b>NT K</b>	Chisel tip	1,2 mm	0,4 mm	8,4 mm		
NT A	<b>NT A</b>	Chisel tip	1,6 mm	0,4 mm	9,5 mm		
NT 6	<b>NT 6</b>	Chisel tip	1,6 mm	0,7 mm	7,4 mm		
NT B	<b>NT B</b>	Chisel tip	2,4 mm	0,8 mm	7,8 mm		
NT C	<b>NT C</b>	Chisel tip	3,2 mm	0,8 mm	8,2 mm		
NT D	<b>NT D</b>	Chisel tip	4,0 mm	0,8 mm	8,6 mm		
NT AX	<b>NT AX</b>	Chisel tip bent	1,6 mm	0,4 mm	8,2 mm		
NT 1S	<b>NT 1S</b>	Round tip slim	Ø 0,25 mm		8,5 mm		
NT 1	<b>NT 1</b>	Round tip	Ø 0,25 mm		7,4 mm		
NT 1X	<b>NT 1X</b>	Round tip bent 45°	Ø 0,4 mm		8,6 mm		
NT 4	<b>NT 4</b>	Round tip sloped 45°	Ø 1,2 mm		9,9 mm		
NT GW	<b>NT GW</b>	Gullwing tip	2,0 mm	3,0 mm	13,4 mm		
NT MS	<b>NT MS</b>	NT Measuring tip for thermoelement Ø 0,5 mm					

Order-no.	Description	
T005 87 517 17	Silicon pad for changing bent NT tips	
T005 87 517 10	Tip changing tool for changing straight NT tips	