

ELS-950 Series Rugged Electro-Optic Level Sensors

The ELS-950 Series represents Gems' smallest electro-optic level sensors developed to monitor a broad range of media including OHV type fluids.

Our UL-approved design features a TPE over-molded electronics insert, TPE insulated wires, and fluorocarbon o-ring seals that create a watertight, environmentally resistant assembly, ideally suited for use in harsh environments offering excellent temperature and pressure capabilities.

The ELS-950 is excellent for industrial OEMs requiring a solid-state sensor for small space and high temperature environments.

Specifications

Materials Housing	Polysulfone (Contact Gems for alternative material types)			
Prism	Polysulfone			
0-Ring	Fluorocarbon (1/4" MNPT - None)			
Electronics	Over-molded TPE			
Operating Pressure	0 to 250 PSI (0 to 17 bar) maximum			
Operating Temperature*	-40°F to +230°F (-40°C to 110°C)			
Current Consumptions (No L	.oad)			
5 VDC	4 mA No Load			
12 VDC	10mA No Load			
Output	Sink 40 mA max., up to 30 VDC			
Repeatability	±1 mm			
Lead Wires	3x TPE Insulated; 22 AWG			
Approvals	CE, UL file No. E108913			
	IP66/67 Rating			
	ROHS Compliant			

^{*} These switches are not for use in freezing liquids or steam/high condensation environments. Contact Gems for alternative solutions.

How To Order

Specify Part Number based on Input and Output Condition required.

Input Actuation Power Condition	Lead Wire Length	Mounting Type		
		1/4" MNPT	1/2"- 20UNF-2B*	M12x1-8*
5 VDC ±10% Wet	6 inches	224504 🗲	224501 🗲	224508 🗲
	2 meters	226545	226541	226549
	6 inches	224505	224502 🗲	224509
	2 meters	226546	226542	226550
12 VDC ±10%	6 inches	224506 🗲	224503 🗲	224510 🗲
	2 meters	226547	226543	226551
	6 inches	224507 🗲	223625 🗲	224511 🗲
	2 meters	226548	226544	226552
	Condition Wet Dry Wet	Condition Length Wet 6 inches 2 meters 6 inches Dry 2 meters Wet 6 inches 2 meters 6 inches 2 meters 6 inches	Condition Length 1/4" MNPT Wet 6 inches 224504 # 2 meters 226545 Bory 6 inches 224505 2 meters 226546 Wet 6 inches 224506 # 2 meters 226547 6 inches 224507 #	Condition Length 1/4" MNPT 1/2"-20UNF-2B* Wet 6 inches 224504 /r 224501 /r 2 meters 226545 226541 Dry 6 inches 224505 224502 /r 2 meters 226546 226542 Wet 6 inches 224506 /r 224503 /r 2 meters 226547 226543 6 inches 224507 /r 223625 /r


Supplied with standard fluorocarbon o-ring.



Typical Applications

- · Coolant reservoir monitoring and warning
- Medical diagnostic, sterilizer, washers and dialysis equipment
- Low lubricant warning on machine tools, generator sets, on- or off-highway vehicles
- •Low level warning in hydraulic reservoirs
- · Plastic over flow bottles, plastic radiators
- · Leak detection for drip pans

Dimensions



Wiring Diagrams

