


NUT



7. Nut	2.3T Brass	1	Nickel Plated
6. Insulator	1.0T Bakelite	1	Natural
5. Housing	PBT-94V-0	1	Black
4. Pin(2.5φ)	Copper	1	Nickel Plated
3. Break Terminal	0.3T Brass	1	Silver Plated
2. Sleeve Spring	0.2T Phosphor Bronze	1	Silver Plated
1. Pin Terminal	0.4T Brass	1	Silver Plated
NO.	Description	Material	Q'TY



S.C. PRECISION INDUSTRIAL CO., LTD.

PART NAME : DC POWER JACK

PART NUMBER:SCD522DCS100BVG

VERSION:2.0

TOLERANCE :±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT:mm

SCALE:1/1

DATE	DWN	CHKD	APVD	MANAGER
01.20.2011	李世強	陳國強	李國強	李國強

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Current Rating : Max 2.0A , 16VDC
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲ : The Most Important Dimension

RoHS Compliant

1 2 3 4 5 6 7