





## LED Distribution Box terminaLED®

### terminaLED® S 3050 - triple distribution box for LED spots in series connections



[Click here for PDF view](#)

### Technical data

- Connection** IDC (insulation displacement connector)  
3 x 2 clamping units 0.34 – 0.5 mm<sup>2</sup>  
(IN, LED, OUT)
- Fixing** centrally by screw M3,5 or with a glued rear side
- Mouldings** polyamide 6/6, light grey  
flammability rating to UL 94: V-2  
continuous working temperature 100 °C  
short-time temperature 160 °C
- Cables** XYFAZ 2 x 0.5 mm<sup>2</sup>, flexible  
twin cable red/black  
on reels, 50 metres or 100 metres  
to be ordered separately as accessories
- Contacts** bronze, plated
- Voltage rating** 150 V according EN 60 598-1
- Current rating** 6 A (0.5 mm<sup>2</sup>) resp. 5 A (0.34 mm<sup>2</sup>) at T 60 °C
- Protection class** IP 20

### Order info

Description	Item	Order No.	PU	
LED distribution box	terminaLED® S 3050	601103	50	>
Cables 50 metres	XYFAZ 2 x 0,5 50	609950	1	>
Cable 100 metres	XYFAZ 2 x 0,5 100	6099X0	1	>