

PCWork PCW03A True RMS Smart Digital Multimeter

Our new flagship model: PCW03A True RMS Smart Digital Multimeter

Perfect for electricians, other professionals & ambitious hobbyists

- CAT III 1000V; CAT IV 600V
- 9999 counts & True RMS
- Auto Range & smart measurement function: device automatically recognizes intended measurement (continuity, voltage, resistance)
- LED illuminated input sockets (indicating correct input sockets for measurement)
- AC/DC voltage, current, resistance, capacitance, frequency, duty ratio, and temperature measurement
- NCV (non-contact voltage), live line, continuity, and diode test
- Double insulation, ceramic fuses, & removable rubber casing
- Large colour HD display with backlight
- Data hold with Min/Max function & LED work light
- Innovative design and 5 button operating concept: like a smartphone
- Great packaging design and manual with pictures in various languages: EN, GER, ES, FR, PT, PL, IT
- Includes batteries, high-quality test leads, K-type temp. probes & transport case



Design like a smartphone

PCW03A Technical Data:

DC Voltage:	99,99mV/999,9mV/9,99V/99,99V/999,9V $\pm(0,5\%+3)$
AC Voltage:	99,99mV/999,9mV/9,99V/99,99V/999,9V $\pm(0,8\%+3)$
DC Current:	99,99uA/999,9uA/99,9mA/999,9mA $\pm(0,8\%+3)$; 9,99A $\pm(1,2\%+3)$
AC Current :	99,99uA/999,9uA/99,9mA/999,9mA $\pm(1,0\%+3)$; 9,99A $\pm(1,5\%+3)$
Resistance:	99,99 Ω /999,9 Ω /9,999k Ω /99,9k Ω /999,9k Ω $\pm(0,8\%+3)$; 9,999M Ω /99,99M Ω $\pm(1,2\%+3)$
Capacitance:	9,999nF/99,99nF/999,9nF/9,999 μ F/99,99 μ F/999,9 μ F $\pm(4,0\%+3)$; /9,999mF/ 99,99mF $\pm(5,0\%+5)$
Frequency:	99,99Hz/999,9Hz/9,999kHz/99,99kHz/999,9kHz/9,99MHz $\pm(1,0\%+3)$
Duty:	0,1%~99,9% $\pm(1,0\%+2)$
Temperature (°C):	-40°C~1000°C $\pm(1,0\%+3)$
Power Supply:	3*1.5V AAA Batteries; Auto Power-Off function
Size:	165*85*25mm
Weight:	255g
Safety Rating:	CE; EN61010-1,-2-030,-2-033; EN61326-1,-2-2, EN61000-3-2,-3-3; ROHS: 2011/65/EU and amendment 2015/863/EU; REACH (EC) No. 1907/2006



PCW03A Pictures:

PCWork



Illuminated Color HD Display



LED Worklight



DIGITAL MULTIMETER TRUE RMS

REL HOLD AUTO FUNC RANGE SEL REL HOLD MAX MIN

10A mA COM Live (L-N-P-E) V Hz % C/F

MAX 10A/250V~ MAX 60mA/250V~ MAX 750V~ 1000V~

Illuminated Input Sockets: Device indicates the correct input sockets for each measurement function



Smart Measurement Function:
AC/DC voltage, resistance,
and continuity measurement

PCWork

Professional Functionality
Without Compromises
In an Innovative &
Compact
Design

Product Size



84mm 23mm 84mm 165mm

Double Fuse Protective Design
Maximum Security & Protection



Shock-Absorbant Protective Cover
Made From Industrial-Grade PVC Rubber



PCW03A Pictures:

PCWork

Smart Measurement Function:
AC/DC voltage, resistance,
and continuity measurement



PCWork

DOMESTIC MEASUREMENT



PCW03A Pictures:

