

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® C141 1x0,35 (75Ω) + 2x0,22 mm² Special Video Flat Divisible Cable



CATEGORY Video + Audio Cables (See Video Catalogue)
APPLICATIONS Video and Audio Stereo assembly

A: Night Blue Soft **PVC** Sheath.
 Outer Dimension: 6,10x13,60 (±0,20) mm.

Audio Section:

B: Spiral shielding in of O.F.C. red copper, covering 100%.
C: Insulations with PVC, colored one red and one white.
 Diam. Ø 1,50 (±0,20) mm.
D: Stranded O.F.C. red copper formation 20x0,12 mm..
 Nom. Cross section 2x0,22 mm².

Video Section:

E: Braid shielding in of O.F.C. tinned copper, covering 85%.
F: Insulation with White PEE. Diam. Ø 3,60 (±0,20) mm.
G: Stranded O.F.C. red copper formation 30x0,12 mm.
 Nom. Cross section 1x0,35 mm² (75Ω)

MARKING **tasker®** C141 1x0,35 mm² (75W) + 2x0,22 mm² O.F.C. Video and Audio Cable

MILAN S.r.l. a socio unico

Head Office – Export department:

Viale Europa, 74
20090 Cusago (MI) Italy
T. +39 02 9039.4556-4158
F. +39 02 9039.4551
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione

Viale Europa 72 Strada F12
20090 Cusago (MI) Italy
T. +39 02 9039.0037-0059
F. +39 02 9039.0049
www.tasker.it

**CUSTOM
PRODUCTION**

This product may be custom produced also in **L.S.Z.H.** polymer, **PE** or **PUR**.

Audio Section Properties

Conductor Resistance	79,15 Ω/Km
Capacity Core/Core	40 pF/m
Capacity Core/Shield	120 pF/m

General Properties:

Max rated Voltage	49 V
Operative Temperature	-15/+70°C

Video 75 Ω properties

Conductor Resistance	58,00 Ω/Km
Impedence	75 Ω
Velocity of Propagation	66 %
Capacity Core/Shield	67 pF/m

Attenuation dB/100 mt.

50 MHz	15,2
100 MHz	23,6
200 MHz	27,7
400 MHz	40,5
800 MHz	61,5
1000 MHz	81,2

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			