

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it



## Technical Datasheet

# tasker® C122 - 4x0,14 mm<sup>2</sup>

### Spiral Shielded Multi-Conductor Cable



**CATEGORY**      Spiral Shielded Cables (See Audio Catalogue)  
**APPLICATIONS**    Sound Reproduction and Electronics.

- A:**      Black Soft **PVC** Sheath. Outer Diam. Ø 8,00 (±0,20) mm.
- B:**      Inner sheaths on each conductor with red **PVC**.  
             Diam. Ø 2,20 (±0,10) mm.
- C:**      O.F.C. red copper spiral Shielding, covering 100%.
- D:**      **PVC** Core Insulation. Diam. Ø 1,10 (±0,10) mm.  
             Color Code: Black, White, Red, Yellow.
- E:**      O.F.C. Red Copper stranded formation 18x0,10 mm.  
             Nom. Cross section 4x0,14 mm<sup>2</sup>.

**MARKING**      **tasker®** C122 4x0,14 mm<sup>2</sup> O.F.C. Individually Shielded Cable  
**CUSTOM**      This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,**  
**PRODUCTION**    with or without Metallic Armor.

#### Cable Properties

<b>Conductor Resistance</b>	138 Ω/Km
<b>Capacity Core/Core</b>	80 pF/m
<b>Capacity Core/Shield</b>	340 pF/m
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70 °C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS3 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Flexible Limited	Flessibilità limitata	<b>Informazioni</b>	<b>X</b>	Ver. B / 12.06.19
		Outdoor	Esterno			Dynamic (Drag Chain)	Mobile in Catena			
		Outdoor Direct Burial	Esterno Interrato			Dynamic (Torsion)	Mobile in Torsione			