



NB: The MENU (texts & graphics) can change, without advice, from model to model and related with the SW version.

FREQ. RANGE	4 - 2250 MHz	5 - 2610 MHz	5 - 2610 MHz	30 - 2700 MHz	30 - 2700 MHz	700 - 2700 MHz
LEVEL RANGE	28 - 130 dBμV	28 - 130 dBμV	28 - 130 dBμV	35 - 115 dBμV	35 - 115 dBμV	35 - 115 dBμV
STANDARD DVB-T/S/S2/C	•	•	•	•	•	S - S2
STANDARD DVB-T2/T2 LITE	•	•	•	•	•	-
STANDARD DVB-S2 MULTISTREAM	•	•	-	-	-	-
WIDE BAND IN	-	•	•	-	-	-
SAT EXTENSION up to 2.610 MHz	opt.	•	•	-	-	-
DAB & DAB+	opt.	opt.	opt.	-	-	-
CAM C.I.	•	-	-	-	-	-
LTE ANALYSIS	•	•	•	•	•	-
OPTICAL INPUT	•	•	opt.	opt.	-	opt.
H265 HEVC	opt.	opt.	opt.	opt.	-	opt.
SAT EXPERT	•	•	•	•	•	•
TS ANALYZER ETR 101 290	•	-	-	-	-	-
TS RECORDER	opt.	opt.	opt.	-	-	-
MER VS CARRIER	•	•	•	•	•	-
MER	•	•	•	•	•	•
CONSTELLATION	•	•	•	•	•	•
DiSEqC - dCSS - SCR	•	•	•	•	•	•
REFLECTOMETER	•	•	•	opt.	opt.	-
MINISPECTRUM	•	-	-	-	-	-
ECHOES ANALYSIS	•	•	•	•	•	-
ANALOG TV	MEAS & PICT	MEAS & PICT	MEAS (PICT opt.)	MEAS only	MEAS only	-
WI-FI	-	opt.	opt.	opt.	-	opt.
GPS	opt.	-	-	-	-	-
NOISE MARGIN GRAPH	•	•	•	•	•	•
IPTV	opt.	opt.	opt.	-	-	-
ASI IN-OUT	•	-	-	-	-	-
LAN	•	•	•	-	-	-
REMOTE MONITORING	•	•	•	-	-	-
DRIVE TEST	opt.	-	-	-	-	-
DOLBY AC3DD +	opt.	opt.	opt.	opt.	opt.	opt.
VIDEO IN RCA (CVBS)	•	•	•	•	•	-
HDMI OUT	•	•	•	-	-	-
USB	A + B	A + B	A + B	B	B	B
TFT	9"	9"	7" High Brightness	5"	5"	5"
TOUCH SCREEN DISPLAY	•	•	•	•	•	•
WEIGHT & DIMENSIONS	2,6 Kg / 29,0 x 17,0 x 5,5 cm	1,8 Kg / 15,5 x 27,0 x 4,0 cm	1,8 Kg / 27,0 x 15,5 x 4,0 cm	1,4 Kg / 13,0 x 25,5 x 4,0 cm	1,4 Kg / 13,0 x 25,5 x 4,0 cm	1,4 Kg / 13,0 x 25,5 x 4,0 cm
BATTERY CAPACITY	from 2 to 4 hours	from 2 to 4 hours	from 2 to 4 hours	from 2 to 4 hours	from 2 to 4 hours	from 2 to 4 hours
BAG	RUGGED BAG	RUGGED BAG	RUGGED BAG	EASY BAG	EASY BAG	EASY BAG
DOCSIS	DOWN STREAM	DOWN STREAM	DOWN STREAM	DOWN STREAM	-	-